

www.tecnocat.com



WORK SERIES

MV-VOL



Multivoltage electric connection system to work either at 200-500 VAC (50 - 60 Hz) or 24 VDC.

Three-phase power cable, a single phase power cable and a 24 VDC connector are supplied.

* Also included with VR1 (Factory Series) except 24 VDC connector.

M-BOX



Metal box for storage and transportation of the vacuum lifter and its accessories.

* Also included with VR1 (Factory Series).

ALF



Metal hanging extension. It extends the point of attachment of the machine to make the glass stands more vertical.

* Also included with VR1 (Factory Series).





www.tecnocat.com

OPTIONALS

WORK SERIES

FU-P



Plastic covers for vacuum cup. They protect the vacuum cup during inactivity periods.

* Avalaible for all vacuum models.

MI-100



Wireless pushbutton controller according to EN ISO 13849-1. It allows the control of all movements and operations of the machine, providing a high level of safety. It is especially recommended for works at significant height. Standard range 100 m.

* Except VC, VL, VL2 and VR1 (Factory Series).

AL-BOT



Pushbutton with 10 m length cable to control all movements and operations of the machine from long distance.

* Except VC, VL, VL2 and VR1 (Factory Series).

CM-VC | CM-VL | CM-VL2

Optional metal box for each vacuum model.







PICTOGRAMS





ELECTRICAL POWER





4

PNEUMATIC SUPPLY



MAXIMUM LOAD CAPACITY



MAXIMUM LOAD CAPACITY ACCORDING EN-13155



TILTING EQUIPMENT



MANUALLY TILTING EQUIPMENT



PNEUMATIC TILTING EQUIPMENT



MOTORIZED TILTING EQUIPMENT



HYDRAULIC TILTING EQUIPMENT





GLASS MOVEMENT



