



HIGHLIGHT

Electric rotating yoke:
Stepless 3D movement of the arm and yoke.



Models:

Outdoor
High Lifter (HL)
High Lifter Electric (HLE)
High Lifter Electric RT (HLE RT)

OUTDOOR

SL 409 OUTDOOR

LIFTS UP TO 430 KG / 950 LBS

The new SL 409 is efficient and hard working. It saves you the cost of extra hands for mounting of elements like glass, windows, granite, marble. The compact and ruggedized design gets the job done. You get:

- Remote controlled vacuum system
- Speedy tilting
- Save position for repeated mounting
- X/Y movement; the straight movement is easy to control and prevents damages from accidentally bumping into something
- Theft protection, geofencing and remote diagnostics with the built-in Trackunit IoT device
- New gel battery pack
- Enhanced safety features



EXTENSION OF ARM

UP TO 120 CM / 48 IN



LIFTING HEIGHT

UP TO 365 CM / 144 IN



Choose the High Lifter version for additional reach and lifting height

TECHNICAL SPECIFICATIONS

Model	SL 409 Outdoor	SL 409 Outdoor HL	SL 409 Outdoor HLE/HLE RT
Lifting cap. arm in/out	430 / 200 kg - 950/440 lbs	430 / 200 kg - 950/440 lbs	430 / 100 kg - 950 / 220 lbs
Lifting height	3.100 mm / 122 in	3.650 mm / 144 in	3.650mm / 144 in
Extension of arm	600 mm / 24 in	600+600 mm / 24+24 in	600+600 mm / 24+24 in
Tip from horizontal	53° back/131° fwd	53° back/131° fwd	35° back/106° fwd
Side shift	100 mm / 4 in	100 mm / 4 in	100 mm / 4 in
Charging voltage	230 V / 110 V	230 V / 110 V	230 V / 110 V
Charging time	Approx. 10 hrs	Approx. 10 hrs	Approx. 10 hrs
Running period	Up to 10 hrs	Up to 10 hrs	Up to 10 hrs
Front-wheel drive	1500 W AC	1500 W AC	1500 W AC
Suction pads	4 x Ø 300 mm / 4 x Ø12 in	4 x Ø 300 mm / 4 x Ø12 in	4 x Ø 300 mm / 4 x Ø12 in
L x W x H	2500x820x1390 mm 98 x 32 x 55 in	2600x820x1400 mm 102 x 32 x 55 in	2590x820x1430 mm 102 x 32 x 56 in
Curb weight	700 kg / 1540 in	710 kg / 1,570 lbs	720/730 kg / 1590/1610 lbs

BUILD YOUR SMARTLIFT

Foam-filled tyres	Standard
Electric key switch	■
White, non-marking tires	■
Special Color	■
Cordless remote	■
Manual extension (HL)	■
Electrical extension (HLE)	■
Rotation yoke RT (HL RT/ HLE RT)	■

■ Select the options you need